

TYPE XH

The XH machine foot is certified according to the 3A hygienic standard: "88-00" and certified according to the EHEDG hygienic standard TYPE EL - CLASS 1. The patented XH machinefoot is sealing all moveable parts 100 % hygienically, even if the load on the foot is removed. The XH type is approved for machines and equipment for the dairy-, brewery and pharmaceutical industry, applications with the highest demands for hygiene and cleaning. The design of the XH system reduces the cleaning effort to an absolute minimum. The sleeve covers the thread, and also functions as a nut. The machine foot admits slopes up to 10° of floors and equipment. The XH machine foot is marked with the 3A and EHEDG logo. Instructions of mounting/cleaning, the 3A and EHEDG certificate are sent together with the shipment. XH65, XH80, XH105, XH125, XH150

TECHNICAL SPECIFICATIONS (IN)

Total height:	9,57 in
Max height:	8,08 in
Min height:	5,48 in
Adjust:	2,59 in
Nom. Pull:	4.000 N
Nom. Load:	15.000 N
Weight:	-
Thread size:	UNC 5/8-11
Foot Plate dia.:	Ø 3,15 in
Anti-slip Rubber:	Yes
Fixing holes:	None



TYPE XH080-XH5883-RHOX5832

LINK www.ngi.dk/products/product-presentation/?pid=12852

