

# TYPE XHF

The XHF machine foot is certified according to the 3A hygienic standard: "88-00" and certified according to the EHEDG hygienic standard TYPE EL - CLASS 1. The patented machine foot is sealing all moveable parts 100 % hygienically, even if the load on the foot is removed. This System is approved for machines and equipment for the dairy-, brewery and pharmaceutical industry, applications with the highest demands for hygiene and cleaning. The design of the XH-HL-3A-FA machine foot reduces the cleaning effort to an absolute minimum. The machine foot admits slopes up to 10° of floors and equipment. Two standard flanges are on stock. Other flanges and gaskets can be made on enquiry. Please see technical information. XHF80, XHF105, XHF125, XHF150

## TECHNICAL SPECIFICATIONS (IN)

Total height:	11,56 in
Max height:	8,47 in
Min height:	4,54 in
Adjust:	3,937 in
Nom. Pull:	4.000 N
Nom. Load:	32.000 N
Weight:	-
Thread size:	UNC 1-8
Foot Plate dia.:	Ø 4,921 in
Anti-slip Rubber:	Yes
Fixing holes:	None



**TYPE** XHF125-XHF-S1-F1

**LINK** [www.ngi.dk/products/product-presentation/?pid=17394](http://www.ngi.dk/products/product-presentation/?pid=17394)

